

Package: AnomalyScore (via r-universe)

May 23, 2026

Title Anomaly Scoring for Multivariate Time Series

Version 0.1

Description Compute an anomaly score for multivariate time series based on the k-nearest neighbors algorithm. Different computations of distances between time series are provided.

License GPL (>= 3)

Imports dtw, class, astda, transport, marima, TSA, RANN, MASS, mvLSW, stats

Encoding UTF-8

Roxygen list(markdown = TRUE)

RoxygenNote 7.3.1

Config/pak/sysreqs libssl-dev

Repository <https://cuauhtemoctzin.r-universe.dev>

Date/Publication 2024-12-16 12:23:45 UTC

RemoteUrl <https://github.com/cuauhtemoctzin/anomalyscore>

RemoteRef HEAD

RemoteSha 5ae19f63988c3879d8835612614d72f4e8cadfa6

Contents

| | |
|-------------------------------------|----|
| all_bands | 2 |
| Anomalyscoresframe | 3 |
| Cort | 4 |
| DEcort | 5 |
| DEcortNorm | 6 |
| distance_matrix_banddepth | 7 |
| distance_matrix_CGCI | 7 |
| distance_matrix_coherence | 8 |
| distance_matrix_cort | 9 |
| distance_matrix_cortNorm | 10 |
| distance_matrix_dtw | 11 |

| | |
|---------------------------------------|----|
| distance_matrix_mahalanobis | 12 |
| distance_matrix_mvLWS | 12 |
| distance_matrix_PDC | 13 |
| distance_matrix_PMIME | 14 |
| distance_matrix_RGPDC | 15 |
| distance_matrix_wasserstein | 16 |
| DTWcort | 16 |
| dxy_bands | 17 |
| informative_bands | 18 |
| kneighbors_distance_docall | 19 |
| matrix_PDC | 20 |
| mBTS | 20 |
| mBTS_Af_mat | 21 |
| mBTSCGCI | 21 |
| mBTSRGPDC | 22 |
| multilagmatrix | 23 |
| PMIME | 23 |
| sqnorms | 25 |

Index **26**

| | |
|-----------|---|
| all_bands | <i>Pairwise band generation in a multivariate time series</i> |
|-----------|---|

Description

takes all the pairs of series in a multivariate set and compute the band between each pair od series

Usage

all_bands(series)

Arguments

| | |
|--------|--|
| series | A matrix of n columns representing a multivariate time series, each column is a univariate time series |
|--------|--|

Value

a list with two elements the lowerbounds of all $(n)(n-1)/2$ pairs and the upperbounds of the pairwise bands

See Also

Band Depth Clustering for Nonstationary Time Series and Wind Speed Behavior (2018) Tupper et al

Examples

```
X=matrix( rnorm(200), ncol=10 )
all_bands(X)
```

Anomalyscoresframe *Anomaly score computation for a set of distances*

Description

Computes anomaly scores for a selection of different distances for a single dataset.

Usage

```
Anomalyscoresframe(unit, knn, measures, dparams)
```

Arguments

| | |
|----------|---|
| unit | A matrix representing a multivariate time series where each column is a univariate time series. |
| knn | number of nearest neighbors to consider for the anomaly scores |
| measures | vector with the indexes of the selected measures 1=Cort, 2=Wasserstein, 3=Mahalanobis, 4=Normalized Cort, 5=Coherence, 6=PDC, 7=CGCI, 8=RGPD, 9=PMIME, 10=mvLWS, 11=Band depth |
| dparams | a list where each element is a list with all the parameters necessary to compute the selected distances. If the distance does not need further parameters then define an empty list |

Value

A dataframe with the names of series in unit as a column called "series" and the corresponding scores computed for each distance. The rank is ordered with respect to the first measure in the measures index vector

See Also

Guillermo Granados, and Idris Eckley. "Electricity Demand of Buildings Benchmarked via Regression Trees on Nearest Neighbors Anomaly Scores"

Examples

```
unit=matrix( rnorm(500), ncol=5 )
measures= c(1,5,11 ) # Cort, Coherence and Band depth
knn=3
dparams=list(
  list(k=2),
  list( span1=2, span2=2, period = 5),
```

```
list( )  
)  
Anomalyscoresframe(unit, knn,measures, dparams)
```

Cort

Temporal correlation coefficient

Description

Return the temporal correlations of two time series by first taking the lag one differences of each series and the computing the correlation coefficient.

Usage

```
Cort(S1, S2)
```

Arguments

S1 A vector representing a univariate time series
S2 A second vector representing a univariate time series

Value

A coefficient in the interval $[-1, 1]$ representing the lag 1 correlation

See Also

Douzal-Chouakria, Ahlame, and Cecile Amblard. "Classification Trees for Time Series." Pattern Recognition 45, no. 3 (March 2012): 1076-91. doi:[10.1016/j.patcog.2011.08.018](https://doi.org/10.1016/j.patcog.2011.08.018)

Examples

```
S1=rnorm(100)  
S2=rnorm(100)  
Cort(S1, S2)
```

DEcort

Distance based on value and behavior of the time series

Description

Return a weighted distance based on a weighted sum of the Euclidean norm and the temporal correlation coefficient. The distance is inflated in the presence of NA compensating for the lack of information.

Usage

```
DEcort(k, S1, S2)
```

Arguments

| | |
|----|---|
| k | The parameter k controls the contribution of the sum of squares comparison as a value-based metric and the $Cort$ quantity as a behavioral metric; when $k=0$, then the distance is equal to the value-based metric, on the other hand, when $k=6$ the distance is mainly determined by the value of the temporal correlation $Cort$. |
| S1 | A vector representing a univariate time series |
| S2 | A second vector representing a univariate time series |

Value

a non-zero value

See Also

Douzal-Chouakria, Ahlame, and Cecile Amblard. "Classification Trees for Time Series." *Pattern Recognition* 45, no. 3 (March 2012): 1076-91. doi:[10.1016/j.patcog.2011.08.018](https://doi.org/10.1016/j.patcog.2011.08.018)

Examples

```
S1=rnorm(100)
S2=rnorm(100)
k=1
DEcort(k,S1, S2)
```

| | |
|------------|---|
| DEcortNorm | <i>Normalized version of the Cort distance the modification is based on using the coefficient of variation rather than euclidean distance, performed by normalizing by the absolute value of the total differences of the series.</i> |
|------------|---|

Description

Normalized version of the Cort distance the modification is based on using the coefficient of variation rather than euclidean distance, performed by normalizing by the absolute value of the total differences of the series.

Usage

DEcortNorm(k, S1, S2)

Arguments

| | |
|----|---|
| k | The parameter k controls the contribution of the sum of squares comparison as a value-based metric and the $Cort$ quantity as a behavioral metric; when $k=0$, then the distance is equal to the value-based metric, on the other hand, when $k=6$ the distance is mainly determined by the value of the temporal correlation $Cort$. |
| S1 | A vector representing a univariate time series |
| S2 | A second vector representing a univariate time series |

Value

a non-zero value

See Also

Granados-Garcia, and Idris Eckley. "Building Electricity Demand Benchmarking via a Regression Trees on Anomaly Scores"

Examples

```
S1=rnorm(100)
S2=rnorm(100)
k=1
DEcortNorm(k,S1, S2)
```

`distance_matrix_banddepth`*Pairwise distance matrix based on the band depth distance*

Description

Pairwise distance matrix based on the band depth distance

Usage

```
distance_matrix_banddepth(unit)
```

Arguments

`unit` A matrix representing a multivariate time series where each column is a univariate time series.

Value

a matrix with pairwise distances

See Also

Band Depth Clustering for Nonstationary Time Series and Wind Speed Behavior (2018) Tupper et al

Examples

```
X=matrix( rnorm(2000), ncol=10 )
distance_matrix_banddepth(unit=X)
```

`distance_matrix_CGCI` *Pairwise distance matrix based on the conditional Granger causality index*

Description

Pairwise distance matrix of a multivariate time series based on the the conditional Granger causality index distance between two series

Usage

```
distance_matrix_CGCI(unit, pmax)
```

Arguments

| | |
|------|---|
| unit | A matrix representing a multivariate time series where each column is a univariate time series. |
| pmax | maximum order(lag) of the VAR model to be considered |

Value

a matrix with pairwise distances

See Also

Siggiridou, Elsa, and Dimitris Kugiumtzis. "Granger Causality in Multivariate Time Series Using a Time-Ordered Restricted Vector Autoregressive Model." IEEE Transactions on Signal Processing 64, no. 7 (April 2016): 1759-73. doi:[10.1109/TSP.2015.2500893](https://doi.org/10.1109/TSP.2015.2500893)

Examples

```
X=matrix( rnorm(2000), ncol=10 )
pmax=4
distance_matrix_CGCI(unit=X, pmax)
```

distance_matrix_coherence

Distance matrix from a coherence measure

Description

Pairwise distance matrix of a multivariate time series based on computing the squared coherence and transformed it to represent a distance at a specific frequency

Usage

```
distance_matrix_coherence(unit, span1, span2, period)
```

Arguments

| | |
|--------|--|
| unit | A matrix representing a multivariate time series where each column is a univariate time series. |
| span1 | Odd integer giving the widths of modified Daniell smoothers to be used to smooth the periodogram. Refers to the bandwidth of the smoothing process. |
| span2 | Odd integer giving the widths of modified Daniell smoothers to be used to smooth the periodogram. Control another level of smoothing to the spectral density estimation without altering the peaks |
| period | Integer referencing the index of the frequency to use for the distance. It gives the Hertz or periods per unit of time; i.e., if the sampling is per minute, and each hour cycle is the period of interest |

Value

a matrix with pairwise distances

See Also

For more details, check the `astsa` package documentation on CRAN or visit the GitHub repository <https://github.com/nickpoison/astsa>.

Examples

```
X=matrix( rnorm(2000), ncol=10 )
span1=2
span2=2
period=3
distance_matrix_coherence(unit=X, span1, span2, period )
```

distance_matrix_cort *Distance matrix from a pattern recognition distance*

Description

pairwise distance matrix of a multivariate time series based on a value (Euclidean distance) and behavior (temporal correlation) measures

Usage

```
distance_matrix_cort(k, unit)
```

Arguments

| | |
|-------------------|--|
| <code>k</code> | The parameter <code>\$k\$</code> controls the contribution of the sum of squares comparison as a value-based metric and the <code>\$Cort\$</code> quantity as a behavioral metric; when <code>\$k=0\$</code> , then the distance is equal to the value-based metric, on the other hand, when <code>\$k=6\$</code> the distance is mainly determined by the value of the temporal correlation <code>\$Cort\$</code> . |
| <code>unit</code> | A matrix representing a multivariate time series where each column is a univariate time series. |

Value

a matrix with pairwise distances

See Also

Douzal-Chouakria, Ahlame, and Cecile Amblard. "Classification Trees for Time Series." *Pattern Recognition* 45, no. 3 (March 2012): 1076-91. doi:10.1016/j.patcog.2011.08.018

Examples

```
X=matrix( rnorm(200), ncol=10 )
k=2
distance_matrix_cort(k,X)
```

distance_matrix_cortNorm

Normalized distance matrix from a pattern recognition distance

Description

pairwise distance matrix of a multivariate time series based on a value (Coefficient of variation) and behavior (temporal correlation) measures

Usage

```
distance_matrix_cortNorm(k, unit)
```

Arguments

| | |
|------|--|
| k | The parameter <code>k</code> controls the contribution of the sum of squares comparison as a value-based metric and the <code>Cort</code> quantity as a behavioral metric; when <code>k=0</code> , then the distance is equal to the value-based metric, on the other hand, when <code>k=6</code> the distance is mainly determined by the value of the temporal correlation <code>Cort</code> . |
| unit | A matrix representing a multivariate time series where each column is a univariate time series. |

Value

a matrix with pairwise distances

See Also

Guillermo Granados, and Idris Eckley. "Electricity Demand of Buildings Benchmarked via Regression Trees on Nearest Neighbors Anomaly Scores"

Examples

```
X=matrix( rnorm(200), ncol=10 )
k=2
distance_matrix_cortNorm(k,X)
```

distance_matrix_dtw *Normalized distance matrix from dynamic time-warping distance*

Description

pairwise distance matrix of a multivariate time series based on a minimal mapping between two time series weighted by temporal correlation

Usage

```
distance_matrix_dtw(k, unit, maxwindow)
```

Arguments

| | |
|-----------|---|
| k | The parameter k controls the contribution of the sum of squares comparison as a value-based metric and the $Cort$ quantity as a behavioral metric; when $k=0$, then the distance is equal to the value-based metric, on the other hand, when $k=6$ the distance is mainly determined by the value of the temporal correlation $Cort$. |
| unit | A matrix representing a multivariate time series where each column is a univariate time series. |
| maxwindow | the maximum shift allowed between time series points. |

Value

a matrix with pairwise distances

See Also

For more details, check the dtw package documentation on CRAN

Examples

```
X=matrix( rnorm(200), ncol=10 )
k=2
maxwindow=10
distance_matrix_dtw(k,X,maxwindow)
```

distance_matrix_mahalanobis

Pairwise distance matrix based on the mahalanobis distance

Description

Pairwise distance matrix of a multivariate time series based on the Mahalanobis distance between two series, modified to consider the different scales of series

Usage

```
distance_matrix_mahalanobis(unit)
```

Arguments

`unit` A matrix representing a multivariate time series where each column is a univariate time series.

Value

a matrix with pairwise distances

See Also

Prekopcsak, Zoltan, and Daniel Lemire. "Time Series Classification by Class-Specific Mahalanobis Distance Measures." *Advances in Data Analysis and Classification* 6, no. 3 (October 2012): 185-200. doi:[10.1007/s1163401201106](https://doi.org/10.1007/s1163401201106)

Examples

```
X=matrix( rnorm(2000), ncol=10 )
distance_matrix_mahalanobis(unit=X )
```

distance_matrix_mvLWS *Pairwise distance matrix based on the multivariate locally wavelet partial coherence*

Description

Pairwise distance matrix based on the multivariate locally wavelet partial coherence

Usage

```
distance_matrix_mvLWS(unit)
```

Arguments

`unit` A matrix representing a multivariate time series where each column is a univariate time series.

Value

a matrix with pairwise distances

See Also

Park, Timothy, Idris A. Eckley, and Hernando C. Ombao. "Estimating Time-Evolving Partial Coherence Between Signals via Multivariate Locally Stationary Wavelet Processes." *IEEE Transactions on Signal Processing* 62, no. 20 (October 2014): 5240-50. doi:10.1109/TSP.2014.2343937

Examples

```
X=matrix( rnorm(2000), ncol=10 )
distance_matrix_mvLWS(unit=X)
```

distance_matrix_PDC *Distance matrix from a partial directed coherence measure (PDC)*

Description

Pairwise distance matrix of a multivariate time series based on the partial directed coherence among two series. The distance considers both directions of causality and transform it to give 0 in absence of causality between the series.

Usage

```
distance_matrix_PDC(unit, ar, period)
```

Arguments

`unit` A matrix representing a multivariate time series where each column is a univariate time series.

`ar` Integer vector containing all the lags considered for the vector autoregressive model

`period` Integer referencing the index of the frequency to use for the distance. It gives the Hertz or periods per unit of time; i.e., if the sampling is per minute, and each hour cycle is the period of interest

Value

a matrix with pairwise distances

See Also

Guillermo Granados, and Idris Eckley. "Electricity Demand of Buildings Benchmarked via Regression Trees on Nearest Neighbors Anomaly Scores"

Examples

```
X=matrix( rnorm(2000), ncol=10 )
ar=c(1, 2)
period=10
distance_matrix_PDC( unit=X, ar, period )
```

distance_matrix_PMIME *Pairwise distance matrix based on the partial mutual information of mixed embeddings (PMIME) method*

Description

Pairwise distance matrix based on the partial mutual information of mixed embeddings (PMIME) method

Usage

```
distance_matrix_PMIME(unit, Lmax, Tl, nnei, A)
```

Arguments

| | |
|------|--|
| unit | A matrix representing a multivariate time series where each column is a univariate time series. |
| Lmax | : the maximum delay to search for X and Y components for the mixed embedding vector ,default is 5. |
| Tl | : Tl steps ahead that the mixed embedding vector has to explain. Note that if Tl>1 the future vector is of length Tl and contains the samples at times t+1,...,t+Tl ,default is 1. |
| nnei | : number of nearest neighbors for density estimation ,default is 5 |
| A | : the threshold for the ratio of CMI over MI of the lagged variables for the termination criterion. |

Value

a matrix with pairwise distances

See Also

Kugiumtzis, D. "Direct-Coupling Information Measure from Nonuniform Embedding." Physical Review E 87, no. 6 (June 25, 2013): 062918. doi:[10.1103/PhysRevE.87.062918](https://doi.org/10.1103/PhysRevE.87.062918)

Examples

```
X=matrix( rnorm(300), ncol=3 )
Lmax=2
Tl=1
nnei=5
A=.95
distance_matrix_PMIME(unit=X, Lmax, Tl, nnei, A )
```

distance_matrix_RGPDC *Pairwise distance matrix based on the restricted generalized partial directed coherence*

Description

Pairwise distance matrix of a multivariate time series based on the the restricted generalized partial directed coherence distance between two series

Usage

```
distance_matrix_RGPDC(unit, pmax, period)
```

Arguments

| | |
|--------|--|
| unit | A matrix representing a multivariate time series where each column is a univariate time series. |
| pmax | maximum order(lag) of the VAR model to be considered |
| period | Integer referencing the index of the frequency to use for the distance. It gives the Hertz or periods per unit of time; i.e., if the sampling is per minute, and each hour cycle is the period of interest |

Value

a matrix with pairwise distances

See Also

Siggiridou, Elsa, Vasilios K. Kimiskidis, and Dimitris Kugiumtzis. "Dimension Reduction of Frequency-Based Direct Granger Causality Measures on Short Time Series." *Journal of Neuroscience Methods* 289 (September 2017) : 64-74. doi:[10.1016/j.jneumeth.2017.06.021](https://doi.org/10.1016/j.jneumeth.2017.06.021)

Examples

```
X=matrix( rnorm(2000), ncol=10 )
pmax=4
period=3
distance_matrix_RGPDC(unit=X, pmax, period)
```

distance_matrix_wasserstein

Distance matrix from based on the Wasserstein distance

Description

Pairwise distance matrix of a multivariate time series based on the Wasserstein distance between the empirical distribution of the series

Usage

```
distance_matrix_wasserstein(unit)
```

Arguments

`unit` A matrix representing a multivariate time series where each column is a univariate time series.

Value

a matrix with pairwise distances

See Also

For more details, check the transport package documentation on CRAN

Examples

```
X=matrix( rnorm(2000), ncol=10 )
distance_matrix_wasserstein(unit=X)
```

DTWcort

Extention of the dynamic time warping distance

Description

This function uses the `dtw()` function from the `dtw` R package to compute a distance based on the mapping that minimizes the distance between two sets of points, the parameters chosen are the "Manhattan" distance to compute the differences between points and the "sakoechiba" window type. Important note: the `dtw` function does not accept NA values, therefore these types of values are removed.

Usage

```
DTWcort(k, S1, S2, maxwindow)
```

Arguments

| | |
|-----------|---|
| k | The parameter k controls the contribution of the sum of squares comparison as a value-based metric and the $Cort$ quantity as a behavioral metric; when $k=0$, then the distance is equal to the value-based metric, on the other hand, when $k=6$ the distance is mainly determined by the value of the temporal correlation $Cort$. |
| S1 | A vector representing a univariate time series |
| S2 | A second vector representing a univariate time series |
| maxwindow | the maximum shift allowed between time series points. |

Value

A non-negative value representing the distance between two time series

See Also

Douzal-Chouakria, Ahlame, and Cecile Amblard. "Classification Trees for Time Series." Pattern Recognition 45, no. 3 (March 2012): 1076-91. doi:10.1016/j.patcog.2011.08.018

Examples

```
S1=rnorm(100)
S2=rnorm(100)
k=1
maxwindow=20
DTWcort(k,S1, S2,maxwindow)
```

dxy_bands

Band depth distance between 2 time series given a set of bands

Description

Distance based on a depth concept, given a set of bands a modified Jaccard measure is compute between the sets of indices that two series share, the Jaccard distances then are averaged over all informative bands.

Usage

```
dxy_bands(allbands, x, y)
```

Arguments

| | |
|----------|---|
| allbands | a list with two elements the lowerbounds of all $(n)(n-1)/2$ pairs and the upperbounds of the pairwise bands. |
| x | A vector representing a univariate time series |
| y | A vector representing a univariate time series |

Value

A non-negative value representing the distance between two time series, based on the concept of band depth.

See Also

Band Depth Clustering for Nonstationary Time Series and Wind Speed Behavior (2018) Tupper et al

Examples

```
X=matrix( rnorm(200), ncol=10 )
M=all_bands(X)
dxy_bands(M,X[,1],X[,2] )
```

| | |
|-------------------|---|
| informative_bands | <i>indexes where a series is within a specific band</i> |
|-------------------|---|

Description

Return the indicies in which the values of a series x are located within a band b , called the informative bands.

Usage

```
informative_bands(allbands, x)
```

Arguments

| | |
|----------|--|
| allbands | a list with two elements the lowerbounds of all $(n)(n-1)/2$ pairs and the upperbounds of the pairwise bands. Result of the function all_bands |
| x | A vector representing a univariate time series |

Value

A vector with indices

See Also

Band Depth Clustering for Nonstationary Time Series and Wind Speed Behavior (2018) Tupper et al

Examples

```
X=matrix( rnorm(200), ncol=10 )
M=all_bands(X)
informative_bands(M,X[,1] )
```

`kneighbors_distance_docal1`*K-Nearest neighbors algorithm to compute an anomaly score*

Description

The method obtain a distance matrix and find the K-nearest neighbors of each series and sum their distances in the neighborhood. The sum is defined as the anomaly score, the series with higher scores implies their neighbors are far away and such a series is a potential outlier

Usage

```
kneighbors_distance_docal1(knn, distance, dparams)
```

Arguments

| | |
|-----------------------|---|
| <code>knn</code> | number of nearest neighbors to consider for the anomaly score |
| <code>distance</code> | function name of the available distance matrices |
| <code>dparams</code> | a list with all the parameters for the distance matrix |

Value

A list of two elements with the anomaly scores and the distance matrix

See Also

Guillermo Granados, and Idris Eckley. "Electricity Demand of Buildings Benchmarked via Regression Trees on Nearest Neighbors Anomaly Scores"

Examples

```
X=matrix( rnorm(2000), ncol=10 )
distance=distance_matrix_coherence
dparams=list(unit=X, span1=2, span2=2, period = 5 )
knn=5
kneighbors_distance_docal1(knn,distance, dparams)
```

| | |
|------------|--|
| matrix_PDC | <i>Partial directed coherence matrix</i> |
|------------|--|

Description

Partial directed coherence matrix

Usage

```
matrix_PDC(unit, ar)
```

Arguments

| | |
|------|--|
| unit | A Matrix containing the multivariate time series. Each column represents a univariate time series. |
| ar | Integer vector containing all the lags considered for the vector autoregressive model |

Value

An real array of dimensions, ncol(unit), ncol(unit), n, where n is the number of frequencies at which the PDC is estimated.

Examples

```
X=matrix( rnorm(2000), ncol=10 )
ar=c(1, 2)
matrix_PDC(X, ar)
```

| | |
|------|--|
| mBTS | <i>modified Back-in-time Selection for vector AR parameters estimation</i> |
|------|--|

Description

modified Back-in-time Selection for vector AR parameters estimation

Usage

```
mBTS(xM, responseindex, pmax)
```

Arguments

| | |
|---------------|---|
| xM | the matrix of K time series (variables in columns) |
| responseindex | the index of the response variable in $\{1, \dots, K\}$ |
| pmax | maximum order(lag) of the VAR model to be considered |

Value

the matrix of all explanatory lagged variables in the DR model. The sequence of the lagged variables in 'lagM'

See Also

I. Vlachos and D. Kugiumtzis, "Backward-in-time selection of the order of dynamic regression prediction model," J. Forecast., vol. 32, pp. 685-701, 2013.

mBTS_Af_mat

mBTS Vector Autoregressive coefficients fourier transform

Description

DFT Vector Autoregressive coefficients matrix using the mBTS algorithm. This matrix is the base to compute the generalized partial directed coherence

Usage

```
mBTS_Af_mat(xM, responseindex, pmax, freqs)
```

Arguments

| | |
|---------------|---|
| xM | the matrix of K time series (variables in columns) |
| responseindex | the index of the response variable in $\{1, \dots, K\}$ |
| pmax | maximum order(lag) of the VAR model to be considered |
| freqs | frequencies at which the spectral density is estimated |

Value

the matrix of all the Restricted Generalized Partial Directed Coherence index across the series of a multivariate set.

mBTSCGCI

computation of the conditional Granger causality index

Description

computation of the conditional Granger causality index

Usage

```
mBTSCGCI(xM, responseindex, pmax)
```

Arguments

| | |
|---------------|---|
| xM | the matrix of K time series (variables in columns) |
| responseindex | the index of the response variable in $\{1, \dots, K\}$ |
| pmax | maximum order(lag) of the VAR model to be considered |

Value

the matrix of all the conditional Granger causality index across the series of a multivariate set.

See Also

Siggiridou, Elsa, and Dimitris Kugiumtzis. "Granger Causality in Multivariate Time Series Using a Time-Ordered Restricted Vector Autoregressive Model." *IEEE Transactions on Signal Processing* 64, no. 7 (April 2016): 1759-73. doi:[10.1109/TSP.2015.2500893](https://doi.org/10.1109/TSP.2015.2500893)

mBTSRGPDC

Restricted Generalized Partial Directed Coherence

Description

partial directed coherence matrix values based on the mBTS algorithm for estimation of the VAR parameters

Usage

mBTSRGPDC(xM, pmax, freqs)

Arguments

| | |
|-------|--|
| xM | the matrix of K time series (variables in columns) |
| pmax | maximum order(lag) of the VAR model to be considered |
| freqs | frequencies at which the spectral density is estimated |

Value

the matrix of all the Restricted Generalized Partial Directed Coherence index across the series of a multivariate set. #'

| | |
|----------------|-----------------------|
| multilagmatrix | <i>multilagmatrix</i> |
|----------------|-----------------------|

Description

multilagmatrix builds the set of explanatory variables for the dynamic regression model.

Usage

```
multilagmatrix(xM, responseindex, ordersV, indexV)
```

Arguments

| | |
|---------------|---|
| xM | the matrix of K time series (variables in columns) |
| responseindex | the index of the response variable in $\{1, \dots, K\}$ |
| ordersV | vector of size 1xK of the maximum order for each of the K variables. |
| indexV | the vector of size 1 x K <i>pmax of zeros and ones e.g. if the component in position 2pmax+3 is one, the third variable, lag 3, X3(t-3), is selected.</i> |

Value

the matrix of all explanatory lagged variables in the DR model. The sequence of the lagged variables in 'lagM'

See Also

Kugiumtzis, D. "Direct-Coupling Information Measure from Nonuniform Embedding." Physical Review E 87, no. 6 (June 25, 2013): 062918. doi:[10.1103/PhysRevE.87.062918](https://doi.org/10.1103/PhysRevE.87.062918)

| | |
|-------|--|
| PMIME | <i>PMIME Partial mutual information from mixed embedding</i> |
|-------|--|

Description

computes the measure $R_{X \rightarrow Y|Z}$ for all combinations of X and Y time series from the multivariate time series given in matrix 'allM', of size $N \times K$, where Z contains the rest $K - 2$ time series. The components of X, Y, and Z, are found from a mixed embedding aiming at explaining Y. The mixed embedding is formed by using the progressive embedding algorithm based on conditional mutual information (CMI). CMI is estimated by the method of nearest neighbors (Kraskov's method). The function is the same as PMIMEsig.m but defines the stopping criterion differently, using a fixed rather than adjusted threshold. Specifically, the algorithm terminates if the contribution of the selected lagged variable in explaining the future response state is small enough, as compared to a threshold 'A'. Concretely, the algorithm terminates if $I(x^F; w|wemb)/I(x^F; w, wemb) \leq A$ where $I(x^F; w|wemb)$ is the CMI of the selected lagged variable w and the future response state x^F given the current mixed embedding vector, and $I(x^F; w, wemb)$ is the MI between x^F and the

augmented mixed embedding vector $wemb, w$. We experienced that in rare cases the termination condition is not satisfied and the algorithm does not terminate. Therefore we included a second condition for termination of the algorithm when the ratio $I(x^F; w|wemb)/I(x^F; w, wemb)$ increases in the last two embedding cycles. The derived R measure indicates the information flow of time series X to time series Y conditioned on the rest time series in Z . The measure values are stored in a $K \times K$ matrix 'RM' and given to the output, where the value at position (i, j) indicates the effect from i to j (row to col), and the (i, i) components are zero. The library RANN was used for the nearest neighbor estimation of the mutual information

Usage

```
PMIME(allM, Lmax = 5, T1 = 1, nnei = 5, A = 0.03, showtxt = 1)
```

Arguments

| | |
|---------|---|
| allM | the $N \times K$ matrix of the K time series of length N . |
| Lmax | the maximum delay to search for X and Y components for the mixed embedding vector ,default is 5. |
| T1 | $T1$ steps ahead that the mixed embedding vector has to explain. Note that if $T > 1$ the future vector is of length T and contains the samples at times $t+1, \dots, t+T$,default is 1. |
| nnei | number of nearest neighbors for density estimation ,default is 5 |
| A | the threshold for the ratio of CMI over MI of the lagged variables for the termination criterion. |
| showtxt | : if 0 or negative do not print out anything, if 1 print out the response variable index at each run, if 2 or larger print also info for each embedding cycle ,default is 1. |

Value

RM : A $K \times K$ matrix containing the R values computed by PMIME using the surrogates for setting the stopping criterion. ecC : cell array of K components, where each component is a matrix of size $E \times 5$, and E is the number of embedding cycles. For each embedding cycle the following 5 results are stored: 1. variable index, 2. lag index, 3. CMI of the selected lagged variable w and the future response state x^F given the current mixed embedding vector, $I(x^F; w|wemb)$. 4. MI between x^F and the augmented mixed embedding vector $wemb, w$, $I(x^F; w, wemb)$. 5. The ration of 3. and 4.: $I(x^F; w|wemb)/I(x^F; w, wemb)$

See Also

Kugiumtzis, D. "Direct-Coupling Information Measure from Nonuniform Embedding." Physical Review E 87, no. 6 (June 25, 2013): 062918. doi:10.1103/PhysRevE.87.062918

| | |
|---------|---|
| sqnorms | <i>Quadratic multiplication of a matrix M with respect to a matrix A: Conj(M) A M, where Conj() is the complex conjugate function</i> |
|---------|---|

Description

Quadratic multiplication of a matrix M with respect to a matrix A: $\text{Conj}(M) A M$, where $\text{Conj}()$ is the complex conjugate function

Usage

```
sqnorms(M, A)
```

Arguments

| | |
|---|--------------------------------------|
| M | A Matrix of dimension P by P |
| A | A squared Matrix of dimension P by P |

Value

The squared root of the absolute values of the matrix result of the operation $\text{Conj}(M) A M$

Examples

```
M=matrix( rnorm(100), ncol=10 )  
A=matrix( rnorm(100), ncol=10 )  
sqnorms(M, A)
```

Index

[all_bands](#), 2
[Anomalyscoresframe](#), 3

[Cort](#), 4

[DEcort](#), 5
[DEcortNorm](#), 6
[distance_matrix_banddepth](#), 7
[distance_matrix_CGCI](#), 7
[distance_matrix_coherence](#), 8
[distance_matrix_cort](#), 9
[distance_matrix_cortNorm](#), 10
[distance_matrix_dtw](#), 11
[distance_matrix_mahalanobis](#), 12
[distance_matrix_mvLWS](#), 12
[distance_matrix_PDC](#), 13
[distance_matrix_PMIME](#), 14
[distance_matrix_RGPDC](#), 15
[distance_matrix_wasserstein](#), 16
[DTWcort](#), 16
[dxy_bands](#), 17

[informative_bands](#), 18

[kneighbors_distance_docal1](#), 19

[matrix_PDC](#), 20
[mBTS](#), 20
[mBTS_Af_mat](#), 21
[mBTSCGCI](#), 21
[mBTSRGPDC](#), 22
[multilagmatrix](#), 23

[PMIME](#), 23

[sqnorms](#), 25